

TECHNICAL DATA SHEET

VicWallpaper VMT

Public Spaces / Hi-Fi & Home Cinema / Workspaces



Description: -

VicWallpaper VMT offers advanced acoustic and thermal isolation for residential and commercial spaces. Designed for medium to high frequencies, it enhances speech clarity in areas like meeting rooms, living rooms, and classrooms. Made from fire-rated recycled PET, VicWallpaper VMT is quick and easy to install, eliminating the need for specialized labour.

Features: __

- Light weight
- Easy to Install
- Easy to clean and maintain
- High Performance in medium and high frequencies

Available Finishes*: _

Patterns:

- Deck
- Triangles
- Symmetric

Square 30

■ Square 8

Solid Colors:



^{*}Different batches may show a color variation



Dimensions (L x H x W):

- 600 x 600 x 10 mm
- 1200 x 600 x 10 mm

Packaging Information: __

Units/Box : 8

Box Gross Weight: 4.4kg / 9.6kg

Installation: _

Fixation : Silicon Sealant

Place : Wall Raw Material : Pet Wool

Performance: _

Functionality : Absorption


Absorption Frequency: Medium and High Frequencies

NRC : 0.20



TECHNICAL DATA SHEET

Acoustic Performance: —



Fire Compliance: _____

- ASTM-E84 Class A
- BS 476 Part 6 & 7 Class 1
- EN-13501 Part 1 C, s2, d0

Certifications: _





Disclaimers:

Color combinations are available upon request, subject to minimum order quantity (MOQ).

Please note that the dimensions of these panels have a tolerance of \pm -2mm.

Do not apply these panels behind radiators or too close to a heat source.

A slight color variation may occur between different batches.

The product images used are illustrative and may differ from the actual product.