

TECHNICAL DATA SHEET

Flat Panel VMT

Public Spaces / Hi-Fi & Home Cinema / Professional Audio / Workspaces



Description: __

Optimized for medium to high-frequency sound absorption with varied print options making them an excellent acoustic solution for both commercial and residential spaces.

Features: __

- Light weight
- Easy to Install
- Easy to clean and maintain
- High Performance in medium and high frequencies

Available Finishes*: _

- Natural Woods
- Concrete
- Natural Stones
- Nature

Solid Colors:



*Different batches may show a color variation

Dimensions (L x H x W): __

- 600 x 600 x 20 /40 mm
- 600 x 1200 x 20 /40 mm
- 1200 x 2400 x 20mm

Packaging Information: _

Units/Box

Box Gross Weight : 7.8kg / 13.4kg / 8.8Kg / 15kg

Installation: _

Fixation : Silicon Sealant; VicFix Frame; VicFix J Profile; VicSpacer and VicSpacer Plus

Place : Wall Raw Material : Pet Wool

Performance: _


Functionality : Absorption


 Absorption Frequency : Medium and High Frequencies : 20mm: 0.55 / 40mm: 0.70 NRC



TECHNICAL DATA SHEET

Acoustic Performance:





Fire Compliance: _____

- ASTM-E84 Class A
- BS 476 Part 6 & 7 Class 1
- EN-13501 Part 1 C, s2, d0

Certifications: _





Disclaimers:

Bespoke color and design combinations are available upon request, subject to minimum order quantity (MOQ).

Please note that the dimensions of these panels have a tolerance of +/- 2mm.

Do not apply these panels behind radiators or too close to a heat source.

A slight color variation may occur between different batches.

The product images used are illustrative and may differ from the actual product.